

Specification for **30leds 5050SMD strip**

Applications:

Suitable for cove and contour lighting etc. in KTV, hotel, shopping mall, home, cabinet and so on

Features:

1. 5050SMD LED mounted, 30leds/m.
2. 3 types strip, IP33,IP65 and IP67
3. DC12V
4. 115 Viewing angle
5. Certificate: CE,RoHS
6. Warranty: 3years
7. 3leds per unit can be cut
8. Easy installation with double-sided adhesive tape.

1. Model: S1B30


Non-waterproof, IP 33

Size: L5000 X W10 X H2.2 mm


LED Pitch: 33.3mm

Unite Length: 100mm

Max. 5meters per roll



Drawing:



Specification for 30leds 5050SMD strip

2. Model: S2B30


Waterproof with silicone glue, IP 65

Size: L5000 X W10 X H3.3 mm


LED Pitch: 33.3mm

Unite Length: 100mm

Max. 5meters per roll



Drawing:



3. Model: S3B30


Waterproof with silicone tube, IP 67

Size: L5000 X W13 X H4.4 mm


LED Pitch: 33.3mm

Unite Length: 100mm

Max. 5meters per roll



Drawing:



Specification for 30leds 5050SMD strip

Specification:

Model No.	S1B30/ S2B30/ S3B30				
Color	W	R	G	B	Y
Color Temperature (K) Wavelength (nm)	3000/6000/9000	620-625	525-530	465-470	585-590
Working Voltage	DC12V				
Beam Angle	115 degree Viewing Angle				
Brightness (lm/m)	480	150	270	90	135
Current (mA/m)	60	60	60	60	60
Power (w/m)	7.2	7.2	7.2	7.2	7.2
Operating Temperature	-25°C - 60°C				
Storage Temperature	-30°C - 70°C				
IP Grade	IP33/ IP65/ IP67				